

Toshiba Satellite L305-S5946 RAM Replacement

Remove RAM from your Toshiba Satellite L305-S5946.

Written By: Michael Erberich



INTRODUCTION

Use this guide to replace or upgrade RAM cards in your Toshiba Satellite L305-S5946. Replacing your RAM cards will allow you to work with more programs. Doing this requires only removal of the battery as a precursor.



TOOLS:

- iFixit Opening Tool (1)
- Phillips #1 Screwdriver (1)



PARTS:

PC2-6400 2 GB RAM Chip (1)

Step 1 — Battery



 Place the laptop upside-down with the display hinges facing away from you.

Step 2



 Slide the latch for the left battery bay to the left.

Step 3







- Slide the latch for the right battery bay to the right and hold.
- Continue to hold the latch while using a plastic opening tool to lift and remove the battery bay cover.
- Remove the battery.

Step 4 — RAM



- Using a Phillips #1 screwdriver, turn the screw on the RAM cover until you hear a click.
- i This is a captive panel screw and remains with the cover.

Step 5



Remove the RAM cover by inserting the plastic opening tool into the indent and lifting.

Step 6



- Push the white and silver retaining clips away from each side of the RAM card using your fingernails.
 - (i) The RAM card should pop up at an angle.

Step 7



- Pull the RAM card away from the computer.
- Repeat Steps 6 and 7 to remove the other RAM card that may be installed.

To reassemble your device, follow these instructions in reverse order.