




Mac mini Late 2014 Fan Replacement

Replace the fan in a Late 2014 Mac mini.

Written By: Sam Goldheart



INTRODUCTION

Noisy or poorly-performing fan? Use this guide to replace the fan, or remove it for cleaning in your Mac mini Late 2014.



TOOLS:

- [iFixit Opening Tool](#) (1)
- [Spudger](#) (1)
- [TR6 Torx Security Screwdriver](#) (1)



PARTS:

- [Intel Mac mini \(Mid 2011-Late2012\) Fan](#) (1)

Step 1 — Bottom Cover



- The bottom cover is clipped onto three screw posts.
- Pry near, but not right on the screw posts.

Step 2



- Use the plastic opening tool to pry the bottom cover up off of the Mac mini.

Step 3



- Lift and remove the bottom cover.

Step 4 — Antenna Plate



- Remove the following TR6 screws from the antenna plate:
 - Three 4.1 mm screws
 - Three 1.9 mm screws

Step 5



⚠ Do not completely remove the antenna plate; it is still connected to the Mac mini by an antenna cable.

- With the I/O ports facing you, flip the antenna plate to the right to allow access to the antenna cable connector.

Step 6



- Remove the single 3.4 mm T6 screw and washer from the antenna cable.
- ⓘ Be careful not to lose the washer when removing the screw.

Step 7



- Use the point of a spudger to lift the antenna connector straight up off its socket on the airport card.

Step 8



- Carefully pull the antenna cable out from the gap between the power supply and case.

Step 9




- Remove the antenna plate from the Mac mini.


Step 10 — Fan Assembly



- Remove the two 12 mm T6 screws from the fan.
- Loosen the 27 mm T6 captive screw—it will get removed with the fan assembly.

Step 11




 The fan connector is trapped under the edge of the fan and cannot be disconnected until the fan is moved.

 **Do not attempt to remove the fan entirely.**

- Lift the fan straight up to free the captive screw from its hole in the logic board.
- Pull the fan away from the SSD until you can easily access the fan connector.

Step 12



- Use the point of a spudger to lift the fan connector straight up out of its socket on the logic board.

Step 13



- Remove the fan from the Mac mini.

Step 14 — Fan



- Remove the captive screw from the rubber grommet in the fan screw hole.

To reassemble your device, follow these instructions in reverse order.